



www.cecpower.ca

CEC Online UPS - A Series



MODEL	PEA-500	PEA-700	PEA-1000	PEA-1200	PEA-1600	PEA-2000	
INPUT	Voltage(Vac)	220±25%					
	Frequency(Hz)	50/60±10%					
OUTPUT	Power(KVA/KW)	500/300	700/420	100/600	1200/720	1600/960	2000/1200
	Voltage(Vac)	220±10% / 120± 10% (on battery mode)					
	Frequency(Hz)	Synchronizing with input AC while it is normal, and 50±0.5% or 60±0.5% on battery mode.					
	Transfer Time	Typical 5ms, including detection time and switching time					
BATTERY	Voltage(Vdc)	12	12	24	24	36	36/48
	Battery Type	1*7Ah 12V	1*7Ah 12V/Ext	2*7Ah 12V/Ext	External	3*7Ah 12V/Ext	3*9Ah 12V/Ext
OTHERS	Communication Port	RS232, RJ 45 (USB and SNMP adaptor are optional)					
	Display	LCD display shows status of AC input, Inverter , Low battery, Overload and battery Capacity					
	Alarm	Low Battery, Abnormal AC input, UPS failure					
	Protection	Low Battery, Overload, Short-Circuit and Over Temperature					
	Noise (dB)	< 45					
	Temperature	0~40°C					
	Humidity	0~95% , No Condensation					
	Dimension(W*D*H) mm	90*325*165	90*325*165/ 120*395*220	120*395*220		156*450*220	
Weight (kg)	5	5.5/8	11	8	17/13	18/14	

Telephone : +1 416 897 2784

FAX : +1 289 597 0861

Email :info@cecpower.ca