



www.cecpower.ca



CEC Online UPS - C Series

	MODEL	PEC-1000	PEC-2000	PEC-3000	PEC-6000	PEC-1110
INPUT	Voltage (Vac)	220 ± 30%			220 ± 25%	
	Frequency (Hz)	50/60 ± 6% (50/60 Hz Settings)				
	Power Factor	≤ 0.99				
OUTPUT	Power (KVA/ KW)	1000/700	2000/1400	3000/2100	6000/4800	10000/8000
	Phase	0.7			0.8	
	Voltage (Vac)	220/230/240 ± 2%				
	Frequency (Vac)	50/60 ± 0.2% (Battery Mode)				
	Wave Form	Pure Sine Wave , THD < 3% (Linear Load)				
	Transfer Time	0				
	Overload	105 ~ 129% for Seconds, 130% ~ 150% for Seconds, Above 150% for 300 ms			105~125% for 10 Mins, 125%~ 150% for 1Min, Above 150% for 1 Second	
BATTERY	Voltage (Vdc)	36	72 (220V) 96 (120V)	96	192	
	Battery Type	3*7Ah12V /Ext	6*7Ah12V /Ext	8*7Ah12V /Ext	16*7Ah12V /Ext	
OTHERS	Communication Port	RS232 (Dry Contact, USB and SNMP Adaptor are Optional)			RS232, USB and EPO (Dry Contact and SNMP adaptor is optional)	
	Display	LED indicates the Status of UPS (LCD is optional)			LCD & LED Display	
	Alarm	Low Battery, Abnormal Ac input. UPS Failure				
	Protection	Low Battery, Over-load, Short-Circuit and Over Temperature				
	Noise (dB)	< 45			< 60	
	Temperature	0 ~ 40°C				
	Humidity	0~95%, No Condensation				
	Dimension (W*D*H) mm	156*400*220	198*490*347		255*565*700/ 255*565*500	
Weight (Kg)	13/ 6.5	25/14	29/15	69/26	70/27	

Telephone : +1 416 897 2784

FAX : +1 289 597 0861

Email :info@cecpower.ca