



www.cecpower.ca

# CEC Online UPS - F Series



MODEL		PEF-111	PEF-112	PEF-113	PEF-115	PEF-116	PEF-118	PEF-1110	PEF-1115
INPUT	Voltage (Vac)	220 ± 25%							
	Frequency (Hz)	50/60 ±5% ( 50/60 Hz Settings)							
	Phase	Single Phase, Three Wires							
OUTPUT	Power (KVA/ KW)	1000/700	2000/1400	3000/2100	5000/3500	6000/4200	8000/5600	10000/7000	15000/ 10500
	Phase	Single Phase							
	Voltage (Vac)	220/230/240 ± 2%							
	Frequency (Hz)	50/60 ± 0.5% (Battery Mode)							
	Wave Form	Pure Sine Wave , THD < 3% (Linear Load)							
	Transfer Time	0							
	Overload	125% Load For 60 Seconds, 150% Load For 1 Second							
BATTERY	Voltage (Vdc)	48	96	192					
	Battery Type	4×7Ah12V /Ext	8×7Ah12V /Ext	16×7Ah12V /Ext					
OTHERS	Communication Port	RS232 , Dry Contact (USB and SNMP Adaptor are Optional)							
	Display	LCD Display Input Voltage, Output Voltage, Load Capacity, Battery Voltage, Etc. LED Indicates Running Status							
	Alarm	Low Battery, Abnormal Ac input, Low Battery							
	Protection	Low Battery, Overload, Short-Circuit and Over Temperature, Output Low Voltage, Output Over Voltage							
	Noise (dB)	< 55							
	Temperature	0 ~ 40°C							
	Humidity	0~95%, No Condensation							
	Dimension (W*D*H) mm	230-620-470	230×635×690/ 230×620×470					400-800-1180 /300- 470-700	400-800-1180
Weight (Kg)	48/36	74/49	82/56	90/45	91/47	91/47	210/85	288/145	

**Telephone : +1 416 897 2784**

**FAX : +1 289 597 0861**

**Email :info@cecpower.ca**