www.cecpower.ca

CEC Online UPS - G Series

	MODEL	PEG-3110	PEG-3115	PEG-3120	PEG-3130	PEG-3140	PEG-3150
INPUT	Voltage (Vac)	380 ± 25%					
	Frequency (Hz)	50/60 ± 5%					
	Phase	Three Phase: Four Wires + PE					
OUTPUT	Power (KVA/ KW)	10/7	15/10.5	20/16	30/24	40/32	50/40
	Voltage (Vac)	220 ± 1%					
	Frequency (Hz)	50/60 ± 0.5% (Battery Mode)					
	Wave Form	Pure Sine Wave, THD ‹ 3% (Linear load)					
	Transfer Time	0					
	Overload	125% load for 60 Seconds 150% Load for 1 Second		125% Load for 60 Seconds, 150% Load for 20 Seconds			
BATTERY	Voltage (Vdc)	192		348			
	Battery Type	32×7Ah12V /Ext	48×7Ah12V /Ext	External			
OTEHRS	Communication Port	RS232/485 , Dry Contact (MODBUS and SNMP Adaptor are Optional)					
	Display	LCD Display Input Voltage, Output Voltage, Load Capacity, Battery Voltage, Etc. LED Indicates Running Status					
	Alarm	Low Battery, Abnormal Ac input. Low Battery					
	Protection	Low Battery, Overload, Short-Circuit and Over Temperature, Output Low Voltage, Output Over Voltage					
	Noise (dB)	‹ 60		‹ 65			
	Temperature	0 ~ 40◦c					
	Humidity	0~95%, No Condensation					
	Dimension (W*D*H) mm	400×800×1180 / 300×740×700	400×800×1180				
	Weight (Kg)	250/130	320/195	205	225	273	304

Telephone : +1 416 897 2784
FAX : +1 289 597 0861
Email :info@cecpower.ca