



www.cecpower.ca



# CEC Online UPS - H Series

MODEL		PEH-3310	PEH-3320	PEH-3330	PEH-3340	PEH-3350	PEH-3360	PEH-3380	
INPUT	Voltage (Vac)	380 ± 20%							
	Frequency (Hz)	40~65							
	Sync Frequency	50/60 ± 5% (±10% Optional)							
	Phase	Three Phase: Four Wires + PE							
OUTPUT	Power (KVA/ KW)	10/8	20/16	30/24	40/32	50/40	60/48	80/64	
	Phase	Three Phase: Four Wires + PE							
	Voltage (Vac)	L-N: 220/230 ± 1%, L-L: 380/400 ± 1%							
	Frequency (Hz)	50/60 ± 0.5% (Battery Mode)							
	Wave Form	Pure Sine Wave, THD < 3% (Linear load)							
	Voltage Stability	≤ 2%, Allow 100% unbalance							
BATTERY	Voltage (Vdc)	348/ 360 (Adjustable)							
	Battery Type	29*7Ah12V Or 30*7Ah12V							
	Battery Testing	Automatically alarm and estimate battery status in battery abnormal status							
OTHERS	Manual Bypass	Yes							
	Communication Port	RS232/RS485 , Dry Contact (MODBUS and SNMP Adaptor are Optional)							
	Display	LCD Display Input Voltage, Output Voltage, Load Capacity, Battery Voltage, Etc. LED Indicates Running Status							
	Alarm	Overload, Abnormal AC input, Low Battery , UPS Failure							
	Protection	Low Battery, Overload, Short-Circuit and Over Temperature, Output Low Voltage, Output Over Voltage							
	Noise (dB)	< 65							
	Temperature	0 ~ 40°C							
	Humidity	0~95%, No Condensation							
	Dimension (W*D*H) mm	500*800*1180			800*800*1600			1000*800*1800	
	Weight (Kg)	195	240	290	450	470	490	690	

Telephone : +1 416 897 2784

FAX : +1 289 597 0861

Email :info@cecpower.ca